

## **Investigation of the spatial distribution of runoff generation and soil erosion processes by means of experimental methods in forested small-catchments**

Verena BUTZEN<sup>1</sup>, Markus CASPER<sup>1</sup>, Margret JOHST<sup>1</sup>, Christoph MUELLER<sup>2</sup>, Marco HÜMANN<sup>2</sup>,  
Ralph HANSEN<sup>1</sup>, Manuel SEEGER<sup>3</sup>, Johannes B. RIES<sup>1</sup>, Stefan WIRTZ<sup>1</sup> & Thomas ISERLOH<sup>1</sup>

<sup>1</sup>Department of Physical Geography, Trier University, Trier (Germany), email: butzen@uni-trier.de;

<sup>2</sup>Department of Soil Sciences, Trier University, Trier (Germany); <sup>3</sup>Department of Land Degradation and Development, Wageningen University, Wageningen (The Netherlands)

According to research results of the last decades forests can contribute appreciably to the genesis of flood events and soil erosion processes, mainly depending on their management and relief position. This fact is becoming crucial when facing the expected climatic change, considering the presumed increasing frequency of heavy rainfall events in winter. Therefore, it is more and more important to get a spatially distributed quantitative understanding of the processes occurring within a forested catchment. Hence, a combination of several experimental methods addressing different processes has been applied within three forested catchments, the Huewelerbach in Luxemburg as well as the Frankelbach and the Holzbach in Rhineland-Palatinate, Germany.

Experimental measurements as well as mappings of geomorphodynamics and soils were carried out in order to assess the spatial variation and intensity of runoff-generation and soil erosion processes.

The used experimental methods are a slope-scale and a small-plot scale rainfall simulator, single-ring infiltrometer measurements and rill erosion experiments.

By means of the slope-scale rainfall simulator overland flow, as well as subsurface flow in two different depths is measured, whereas the plot scale rainfall simulator measures overland flow generation and suspended sediment load. The infiltration measurements with a single ring infiltration device with float-regulated water height delivers data on infiltration capacity of the soils.

By means of the rill erosion experiments the effectiveness of the studied harvester tracks as flow paths for concentrated overland flow is tested as well as the erosion in these tracks. The rill erosion experiments enable a comparison of the processes and erosion amounts produced in the rill or rut for a defined runoff inflow. The catchment of the rill is approximated in order to enable an estimation of the water amounts that might reach the rill during heavy rainfall events. The reaction of the rill catchment is tested by means of the rainfall simulation experiments and infiltration measurements.

By means of all these experimental measurements in combination with a detailed geomorphologic mapping, it becomes possible to determine the spatial distribution of overland-flow generating areas and the occurrence of possible soil erosion processes in the study area.