### **■** Universität Trie




Introduction and Main Objective

# Design and calibration of the small portable rainfall simulator of Trier University

WAGENINGEN UNIVERSITEIT

WAGENINGENUR

T. Iserloh (1), W. Fister (2), J.B. Ries (1), M. Seeger (3)



## Rainfall Regulation (current version)

1) Average spatial rainfall distribution a) and spatial rainfall variability b)

Concentric Pattern

→ Lowest intensities in the centre highest intensities at the rim

Because of better spraying characteristics, the previously used hollow cone nozzle (Hardi Syntal 1553-89 10) has been exchanged by a full cone by a flow meter and needle valve. water flow and pressure with a conventional valve to an exact regulation nozzle (Lechler 460.608). The rainfall regulation changed from regulating rainfall distribution, better drop spectrum and reproducibility of both was methodically improved in 2008/09 aiming on homogeneous spatial been used in Germany, Spain, Morocco and Burkina Faso since 1995. The small portable nozzle-type rainfall simulator of Trier University has

## Calibration Methods

から できる





3) Rain Gauges 2) Calibration Plate Rainfall intensity

1) Laser Disdrometer (Thies) 

Drop sizes/-fall velocities

Spatial rainfall distribution

## Main Parts of the Rainfall Simulator

Nozzle-type Rainfall Simulator based on design by Calvo Cases et al. (1988) and Lasanta et al. (1994) ntensity 40 mm h

Nater Tank (max. 100 Pump max. 20 bar

flotor (97 cm<sup>3</sup>) otor Pump
















## Rainfall Regulation (former version)

Hardi Syntal 1553-89 10 Conventional Valve










### 1) Spatial rainfall distribution

- Drop size distribution and fall velocity → Clearly heterogeneous and not reproducible rainfal
- → Low similarities with natural rainfall (velocity of small
- drops is too high, velocity of large drops is too low)


Contact: Dipl.-Umweltwiss. Thomas





2a) Average drop size distribution and fall velocity on five positions [see 1)]

Average deviation from mean (%)



- 2a) → Complete naturally occurring drop spectrum is covered → The velocities of smaller drops often are similar to that of
- → Due to low fall heights, larger drops are too slow compared to natural rainfall droplets, maximum velocities: 3.4 to 5 m s-

natural ones.

- → Good reproducibility → Very low deviations where most drops are measured


2b) Drop size distribution and fall velocity: 2c) Drop size distribution variability 5.1 % -10.0 % maximum variability of 6.4 % 15 %

Very good reproducibility → Christiansen Uniformity 91 %

**Deviation Class** 

0%-5.0%

85 %



- 2 b) → Highest deviations where the least drops are measured
- → Variability on total plot is caused by concentric rainfall distribution pattern
- and Marshall Palmer Distribution
- 2 c) → Drop distribution corresponds approximately to Marshall & Palmer Distribution (Marshall & Pa
- → Good reproducibility: Max. variability of drop amount is 28% in drop diameter class 0-0.49

### Conclusions

- → Modifications clearly improved reproducibility as well as drop characteristic of artificial rainfall
- → Due to general physical limitations a still better simulation of natural rainfall is not possible with this device
- → The new setup proved worthwhile in laboratory tests and in field campaign

54286 Trier, Gennary, Phone: +49/(0)651 201-3390, E-ma